

S-40 SERIES / Pathological Microscope

Specifications

Head	Monocular head, 30° inclined & 360° rotating Binocular head, 30° inclined & 360° rotating Trinocular head of free compensation, 30° inclined & 360° rotating
Eyepiece	Wide-field eyepiece WF10X-18mm, paired
Nosepiece	Quadruple nosepiece with built-in click stopper
Objective	Achromatic objectives 4X/0.10, 10X/0.25, 40X(S)/0.65, 100X(S,O)/1.25 Plan achromatic objectives P4X, P10X, P40X(S), P100X(S,O)
Stage	Built-in mechanical stage 155mm X 142mm, moving range 50mmX76mm, with specimen holder.
Condenser	N.A.1.25 Abbe condenser focusable by rack & pinion, iris diaphragm, filters and filter holder
Illumination	Built-in electrical illuminator with a halogen bulb 20W/6V, a power switch, a fuse T1A & fuse holder, a power socket, a power cable. Main power input: 85V-265V.
Focusing	Coaxial focusing system with built-in tension adjustment & focus stopper for preventing damage to slides and objectives
Optional	Phase contrast: achromatic objectives 10X, 20X, 40X, 100X(S,O)
Accessories	Phase contrast: plan achromatic objectives 4X, 10X, 40X, 100X(S,O);
Packing	Each set in a foam in a carton



NILPA CONSULTANCY